

AGRO DIGITAL MOISTURE METER (PRO)



Features:-

- Confirms to IS: 8824 with upto date amendments.
- Mild Steel Body & Test Cup.
- Polydome switches keypad .
- Interactive UI , easy to operate .
- Direct Reading , no need for mathematical calculations .
- Calibrated for 60 Crops.
- Last Reading Recall , Averaging, Auto Calibration, Date & Time facility available in MENU button.
- Pressure and Vol cup information displayed on LCD Display.
- Manual On/Off with on off button.



MODEL - AB-2020

Specifications:-

- | | |
|---|---|
| <ol style="list-style-type: none">1. Type2. Principle of Measurement3. Sensor4. Measured Parameters5. Calibration6. Range7. Accuracy8. Display9. Resolution10. Temperature Sensor11. Temperature Measurement Range12. Operating Temperature13. Data Storage14. Real Time Clock15. Humidity Measurement16. Keypad17. Hot Keys18. Error Correction Facility19. Power Supply20. Data Transfer21. Weight22. Dimensions23. Mobile App & PC Software for data printing24. Receipt Printing25. Packing | <ul style="list-style-type: none">- Benchtop/Table Model with Mild Steel Body/Compression Unit- Resistance/Conductivity Measurement- Cup Type- Moisture, Room Temperature, Humidity- Manual and Automatic Both- 3.5 - 40%- $\pm 0.20\%$- 2x16 col LCD- 0.1- PT-100 / LM335 Optional- Automatic- 0-60 °celsius- 200 readings- Inbuilt- Optional- 9 Keys membrane keypad with polydome switches- 3 user programmable hot keys- Inbuilt alongwith new commodity calibration- 9 volts dc through adaptor or 1.5 V x 6 dry cell- Through RS- 232 Port to Printer and Personal Computer- 9.5 Kgs Apprx.w/o accessories- 30x17x26 (LxBxH) cms apprx.- Through iSmart Software.- Through Serial Printer for printing Receipt Data (Party Name, Lot No, Date, Time, Commodity Name , Moisture % and Depositor Name)- Wooden Box supplied with 3 Volume cups , Adaptor, Ratchet Handle, Dust Cover and Operation Manual |
|---|---|

A-GRAIN (INDIA)

27-A, Shivaji Park, opp. Sec-9, Ambala City-134003

 www.moisturemeterstore.in

 **9996081859**

 sales@gmail.com

